



## Power Angle Broom

The Power Angle Broom is designed for heavy-duty sweeping of dirt, snow, and other unwanted material. It quickly mounts to your skid steer or tractor loader. Featuring a 68", 84" or 96" width, optional hydraulic angle change, and the exclusive Floating Torsion Suspension System™.



*The exclusive E-Z Sweep Floating Torsion Suspension System™ assists the operator in keeping consistent and correct bristle down-pressure, reducing excessive wear on the bristles.*

### FEATURES

- Easy operation
- Exclusive Torsion Float Suspension
- Fast wafer change time
- Manual 25° right and left angle
- Optional hydraulic angling 25° right and left angle
- Greasable bearings for longer wear life
- Hydraulic drive motor (no chains) mounted in brush arbor
- Loader arms raise and lower broom
- Large 32" heavy-duty wafer packages available



*"A Legacy of Excellence Since 1948"*

[www.erskineattachments.com](http://www.erskineattachments.com)

# SKID STEER



## SPECIFICATIONS / OPTIONS

Model	680 / 680X / 680XL	840 / 840X / 840XL	960 / 960X / 960XL
Width	68"	84"	96"
Width Fully Angled	63" @ 25°	77" @ 25°	89" @ 25°
Broom Angling	Manual 25°	Manual 25°	Manual 25°
Drive System	Hydraulic Motor Direct Drive	Hydraulic Motor Direct Drive	Hydraulic Motor Direct Drive
Flow Range	13-24 GPM	13-24 GPM	10-20 GPM
Wafer Diameter	32"	32"	32"
Wafer Sections (number)	33 zig-zag, 2 straight	40 zig-zag, 2 straight	48 zig-zag, 2 straight
Mounting Plate	Universal	Universal	Universal
Shipping Weight	790 lb.	850 lb.	910 lb.
Operating Weight	715 lb.	775 lb.	835 lb.

### Options

Pistol Grip Control Harness

Loader Specific Wire Harness\*

Factory Installed Couplers

Model	Model	Model
680 Manual w/poly	840 Manual w/poly	960 Manual w/poly
680 Manual w/steel	840 Manual w/steel	960 Manual w/steel
680 Manual w/poly/steel	840 Manual w/poly/steel	960 Manual w/poly/steel
680X Hyd. w/poly	840X Hyd. w/poly	960X Hyd. w/poly
680X Hyd. w/steel	840X Hyd. w/steel	960X Hyd. w/steel
680X Hyd. w/poly/steel	840X Hyd. w/poly/steel	960X Hyd. w/poly/steel
680XL Hyd. Rev. w/poly	840XL Hyd. Rev. w/poly	960XL Hyd. Rev. w/poly
680XL Hyd. Rev. w/steel	840XL Hyd. Rev. w/steel	960XL Hyd. Rev. w/steel
680XL Hyd. Rev. w/poly/steel	840XL Hyd. Rev. w/poly/steel	960XL Hyd. Rev. w/poly/steel

\* Applies to Hydraulic Models Only

Easily assembled  
**greasable bearings** for  
extended wear life



**Optional:**  
Wire harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/CASE/Bobcat (14-pin)



**Optional:**  
Pistol Grip Control Harness is required if skid steer is **NOT** equipped with attachment control system. (Only needed when ordering hydraulic angling model).

**FAT•N** | Char-Lynn

**ERSKINE**  
ATTACHMENTS LLC

Prices, financing and specifications subject to change without notice.

“For the Lord takes delight in his people; he crowns the humble with victory.” – Psalm 149:4